

AEON-TX

AEON HEVC Transmitter

Overview:

A compact and feature-rich COFDM digital video transmitter, specifically designed for high quality wireless link applications. With proven Domo COFDM and next generation HEVC encoder technology at its core enabling Ultra High Definition images the small size and actively cooled enclosure give maximum operational performance. Designed to offer future proof connectivity, the unit supports native 12G-SDI, dual 6G-SDI, quad 3G-SDI, as well as SFP+ expansion. Two true balanced audio inputs are included with phantom power. The transmitter has an integrated control panel with sunlight-readable LCD display covering all major functions and has 16 user-defined presets, as well as IP based control.

The HEVC codec used in AEON products offers a step change in compression efficiency over H.264 systems, whilst maintaining low end to end latency suitable for live events.

Features and Benefits:

Ultra-low latency HEVC SD, HD and 4K encoding

Video formats up to 2160p60, 10-bit and 4:2:2 chroma sampling, future HDR support

Industry standard DVB-T modulation for interoperability with existing systems

Domo Broadcast UMLV modulation for enhanced high frequency/high speed performance

Controlled via IP or integrated sunlight-readable LCD display

Designed for sports & events coverage, newsgathering and wireless studio camera applications

Integrated return channels for bi-direction IP connectivity and low bandwidth telemetry

Scalable return channel for talk-back to camera control to return video

Low power consumption and active cooling for extended field performance



Product Information:

Product Includes

CA0579	XLR audio input cable
CA3348 x4	12G-SDI HD-BNC to BNC cable 0.25m
SA4075	AEON HEVC support USB stick

Accessory Options (sold separately)

AEON-TX-HDUP	Additional transmitter HD license
AEON-DEC	AEON HEVC Decoder 1/2 1RU Rack
AEON-ENC	AEON HEVC Encoder 1/2 1RU Rack
CA0340	RS232 data input cable
CA3421	0B Lemo 15V 6.0A 90W desktop PSU

Related Documents

100249	AEON HEVC User Guide
--------	----------------------

AEON-TX

AEON HEVC Transmitter

Technical Specification:

IO

SD/HD/3G/6G/12-SDI Inputs	2x HD-BNC
SD/HD/3G-SDI Inputs	2x HD-BNC
ASI Input	HD-BNC
ASI Output	HD-BNC
Dual Receiver SFP	SFP slot (12G-SDI host non-MSA)
Talkback Audio	2x 3.5mm jack **
Camera Interface	10-way circular Hirose **
Camera Tally	5-way 0B Lemo **
Serial Data Input	4-way 0B Lemo (CA0340 9-way D-sub) **
Power Input	4-way 0B Lemo (CA0002 2 x banana)
Balanced Audio Inputs	2x 5-way 0B Lemo (CA0579 2 x XLR3)
Battery Pass-through	V-Lock or Anton Bauer plates
RF COFDM Transmitter	N-type (200mW/100mW modes) *
RF COFDM Transceivers	N-type (2x100mW MIMO capable)
RF Telemetry Transceiver	SMA (20mW typical)
Ethernet	RJ45

DVB-T Modulation

DVB-T Bandwidth	8MHz, 7MHz and 6MHz modes
DVB-T Dual Pedestal	2x8MHz, 2x7MHz and 2x6MHz modes
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T Constellation	QPSK, 16QAM, 64QAM
DVB-T Guard Interval	1/4, 1/8, 1/16, 1/32
DVB-T Bitrates	3.732Mbps to 63.336Mbps

Narrowband/UMVL Modulation

NB Bandwidth	2.5MHz, 1.25MHz and 625kHz modes
UMVL Bandwidth	8MHz, 7MHz and 6MHz modes
NB/UMVL FEC	1/3, 2/3
NB/UMVL Constellation	QPSK, 16QAM, BPSK, 8PSK
NB/UMVL Guard Interval	1/8, 1/16
NB Bitrates	144kbps to 4.879Mbps
UMVL Bitrates	1.317kbps to 14.869Mbps

Telemetry Modulation

Telemetry Bandwidth	4.8kHz mode
Telemetry Sensitivity	-114dBm @ 4.8kHz bandwidth

Video

SD Input Format	SMPTE-259M 720x576i 50Hz 720x480i 59Hz
HD Input Format	SMPTE-292M/424M 1920x1080i 60/59.94/50Hz 1920x1080p 60/59.94/50/30/29.97/25/24/ 23.97Hz 1920x1080psf 30/29.97/25/24/23.97Hz 1280x720p 60/59.94/50Hz
Ultra HD Input Format	SMPTE ST-2081/2082 3840x2160p 60/59.94/50/30/29.94/25/24/ 23.97Hz
HEVC Compression	HEVC/H.265/MPEG-H Part 2 8-bit or 10-bit, 4:2:0 or 4:2:2
H.264 Compression	AVC/H.264/MPEG-4 Part 10
MPEG-2 Compression	H.262/MPEG-2 Part 2
HDR Support	Standards TBC **

Audio

Analogue Audio Input	Two balanced analogue stereo pairs +24dBu max input level
Analogue Phantom Power	48V
Digital Audio Input	SD/HD/3G/6G/12G-SDI de-embedding
Sample Rate	48kHz
Coding Modes	Up to 16 channels (8 pairs) LPCM MPEG Audio Layer 2 ** AAC-LC ** HE-AAC **

Other

RS232 Data Input	1k2 to 115k2, 7/8 bit, no/odd/even parity
Front Panel	Built in LCD with joystick

Encryption

Type	ABS 32-bit as standard
Licensable	AES 128/256-bit (subject to export control)

AEON-TX

AEON HEVC Transmitter

Technical Specification (con't):

Physical

Dimensions	L 190mm (170mm excluding connectors), W 115mm, (105mm excluding connectors), D 55mm (without battery plates) or D 89mm (with V-Lock plates) or D 82mm (with Anton Bauer plates)
Weight	1576g

Power

DC Input	9.2V to 17.8V reverse polarity protected
Power Consumption	Typically 30.0W @ 100mW RF power and 4K video

Environment

Temperature Range	-10 to +50 °C
Humidity	Less than 85% non-condensing

Frequency

198750D-044	1.98-2.70GHz + 6.40-7.50GHz + 410-480MHz
440500-043	4.40-5.00GHz + 433.05-434.79MHz
550600-043	5.50-6.00GHz + 433.05-434.79MHz

Software License Code

Silver (included)	DVB-T, Ultra Mobile Video Link (UMVL), Recording, Streaming, Single HD Encoder
Gold	Silver plus DVB-T2 **
Platinum	Gold plus Single 4K and Quad HD Encoder

* Available on dual-band units only

** Future development

Export of encrypted products is subject to United Kingdom regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 (0) 1489 566 750

DTC – Tampa (Head Office)
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #06-04
Singapore
138562

T: +65 6643 4700

DTC – Brazil
Alameda Araguaia 2
190 – Ed. CEA II – suite 1109
Alphaville - Barueri
São Paulo, Brazil
06455-000

T: +55 11 2321 5055