

AEON-CC

AEON HEVC Transmitter, Camera Control

Overview:

A compact COFDM digital video transmitter with integrated camera control, specifically designed for high quality wireless link applications. With proven Domo COFDM and next generation HEVC encoder technology at its core enabling Ultra High Definition images the small size and actively cooled enclosure give maximum operational performance.

Designed to offer future proof connectivity, the unit supports native 12G-SDI, dual 6G-SDI, quad 3G-SDI. Two true balanced audio inputs are included with phantom power. The transmitter has an integrated control panel with IP based control.

The HEVC codec used in AEON products offers a step change in compression efficiency over H.264 systems, whilst maintaining low end to end latency suitable for live events.



V-mount battery option



Features and Benefits:

- Ultra-low latency HEVC SD, HD and 4K encoding
- Video formats up to 2160p60, 10-bit and 4:2:2 chroma sampling, future HDR support
- Industry standard DVB-T modulation for interoperability with existing systems
- Domo Broadcast UMLV modulation for enhanced high frequency/high speed performance
- Controlled via IP or integrated sunlight-readable LCD display
- Available as V-mount, AB-mount or no battery mount options
- Designed for sports & events coverage, newsgathering and wireless studio camera applications
- Low power consumption and active cooling for extended field performance
- Integrated camera control for wide range of supported manufacturers

Product Information:

Product Includes

AP008822	1/4 wave antenna SMA 433MHz (for camera control)
CA0579	XLR audio input cable
CA3348 x 4	12G-SDI HD-BNC to BNC cable 0.25m

Accessory Options (sold separately)

CA3421	OB Lemo 15V 6.0A 90W desktop PSU
VS-CCCAM-GV-UP	Add Grass Valley control to camera receiver
VS-CCCAM-HIT-UP	Add Hitachi control to camera receiver
VS-CCCAM-IKE-UP	Add Ikegami control to camera receiver
VS-CCCAM-PAN-UP	Add Panasonic control to camera receiver plus 30cm cable
VS-CCCAM-SON-UP	Add Sony control to camera receiver plus 30cm cable
PRORXD-8-2RU-AEON	4K Professional HEVC Receiver and Decoder

Related Documents

100282	AEON HEVC Transmitter, Camera Control User Guide
--------	--

AEON-CC

AEON HEVC Transmitter, Camera Control

Technical Specification:

IO

SD/HD 3G/6G/12G-SDI inputs	HD-BNC x 1
SD/HD 3G/6G-SDI inputs	HD-BNC x 1
SD/HD 3G-SDI inputs	HD-BNC x 2
Power input	4-way OB Lemo
RF COFDM transmitter	N-type
Balanced audio input	5-way OB Lemo
Battery mount	V-Lock or Anton Bauer plates
Ethernet	RJ45 x 2

IO (Camera Control)

Camera interface	10-way circular Hirose
Tally	5-way OB Lemo
RF input	SMA (403-473MHz)

DVB-T Modulation

DVB-T bandwidth	8MHz, 7MHz and 6MHz modes
DVB-T dual pedestal	2x8MHz, 2x7MHz and 2x6MHz modes
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T constellation	QPSK, 16QAM, 64QAM
DVB-T guard interval	1/4, 1/8, 1/16, 1/32
DVB-T bitrates	3.732Mbps to 31.668Mbps

UMVL Modulation

UMVL bandwidth	8MHz, 7MHz and 6MHz modes
UMVL FEC	1/3, 2/3
UMVL constellation	QPSK, 16QAM, BPSK, 8PSK
UMVL guard interval	1/8, 1/16
UMVL bitrates	1.317kbps to 14.869Mbps

Camera Control Demodulation

CC bandwidth	12.5kHz, 20kHz and 25kHz modes
CC constellation	4PSK, GMSK
CC sensitivity	-114dBm @ 25kHz bandwidth -111dBm @ 12.5kHz bandwidth

Video

SD input format	SMPTE-259M 720x576i 50Hz 720x480i 59Hz
HD input format	SMPTE-292M/424M 1920x1080i 60/59.94/50Hz 1920x1080p 60/59.94/50/30/29.97/25/24/ 23.97Hz *1920x1080psf 30/29.97/25/24/23.97Hz 1280x720p 60/59.94/50Hz
Ultra HD input format	SMPTE ST-2081/2082 3840x2160p 60/59.94/50/30/29.94/25/24/ 23.97Hz
HEVC compression	HEVC/H.265/MPEG-H Part 2 8-bit or 10-bit, 4:2:0 or 4:2:2
H.264 compression	AVC/H.264/MPEG-4 Part 10
MPEG-2 compression	H.262/MPEG-2 Part 2

Audio

Analogue audio input	One balanced analogue stereo pair +4dBu max input level
Analogue phantom power	48V switchable
Digital audio input	SD/HD-3G/6G/12G-SDI de-embedding
Sample rate	48kHz
Coding modes	Up to 8 channels (4 pairs) LPCM

Power

DC input	10.6V to 17.8V reverse polarity protected
Power consumption	39W average

Physical

Dimensions	166mm (L), 96.8mm (W), 48mm (D)
Weight	1.15kg

AEON-CC

AEON HEVC Transmitter, Camera Control

Technical Specification (con't):

Environment

Temperature range	-10°C to +50°C
Humidity	Less than 85% non-condensing

Frequency

198270	1.98-2.70GHz
300370	3.00-3.70GHz
640700	6.40-7.00GHz
700750	7.00-7.50GHz

Software License Code

Platinum (included)	DVB-T, Ultra Mobile Video Link (UMVL), Dual Pedestal, Single 4K, Quad HD Encoder
LIC-AEON-PSF	PSF Video Formats

*Additional license feature

Export of encrypted products is subject to United Kingdom regulatory export controls.

DTC – Herndon (Headquarters)
2303 Dulles Station Boulevard
Suite 205
Herndon, VA
20171, USA

T: +1 800 665 4648

DTC – Tampa
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 (0) 1489 566 750

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #05-06
Singapore
138562

T: +65 6339 0508