

Eclipse

HEVC Outside Broadcast Transmitter

Overview:

Based around DTC's industry leading "Single Frame Latency" HEVC H.265 encoding technology, the Eclipse is a compact yet fully-featured outside broadcast transmitter. Operating in DVB-T mode with Dual-Pedestal capability and 200mW output power, the Eclipse offers robust transmission in the most demanding of environments. The Eclipse can transmit single 12G-SDI UHD video or four 3G-SDI HD video with embedded audio. It also offers dual high performance stereo analogue audio inputs with phantom power as well as the option of integrated UHF camera control.



Product Information:

Product Codes

ECLIPSE-xxxxxx	Eclipse OB transmitter, no battery plates
ECLIPSE-AB-xxxxxx	Eclipse OB transmitter, AB battery mount
ECLIPSE-V-xxxxxx	Eclipse OB transmitter, V battery mount
ECLIPSE-CCCAM-xxxxxx	Eclipse OB transmitter with camera control, no battery plates
ECLIPSE-AB-CCCAM-xxxxxx	Eclipse OB transmitter with camera control, AB battery mount
ECLIPSE-V-CCCAM-xxxxxx	Eclipse OB transmitter with camera control, V battery mount

Note: Camera control options below. xxxxxx denotes frequency, see over.

Camera Control Options

ECLIPSE-VS-CCCAM-GV-UP	Grass Valley control software with interface cable
ECLIPSE-VS-CCCAM-HIT-UP	Hitachi control software with interface cable
ECLIPSE-VS-CCCAM-IKE-UP	Ikegami control software with interface cable
ECLIPSE-VS-CCCAM-PAN-UP	Panasonic control software with interface cable
ECLIPSE-VS-CCCAM-SON-UP	Sony control software with interface cable

Base Product Includes

CA0579	Audio 5-way circular to XLR cable
--------	-----------------------------------

CCCAM Product Includes

AP008822	Telemetry antenna SMA, 433MHz
CA3919	CCCAM Ethernet cable

Features and Benefits:

- 4K UHD H.265 HEVC encoding
- HD-SDI capability
- #Single frame latency
- 12G-SDI / *dual 6G-SDI / *quad 3G-SDI input
- DVB-T with dual pedestal capability
- *DVB-T2 support
- *Mesh capable
- *HD/SD video decoding in Mesh mode
- Optional camera control receiver
- 2x100mW output provides transmit diversity
- Multiple frequency band options

- * Future development
- # Receiver dependent

Eclipse

HEVC Outside Broadcast Transmitter

Product Information (cont.):

Accessory Options (sold separately)

Antennas L/S/C-Band	Various N-type to match frequency
CA0340	RS-232 data 4-way circular to 9-way D-sub cable
CA0579	Additional audio 5-way circular to XLR cable
CA3421	Power 4-way circular cable to 15V 90W PSU
CA3348	HD-BNC right-angle to BNC cable
CA3552	HD-BNC straight to BNC cable
ECLIPSE-KIT-AB	AB mount battery plate kit
ECLIPSE-KIT-V	V mount battery plate kit

Technical Specification:

IO

RF COFDM transceivers	N-type (f) x 2 (2x100mW)
RF COFDM transmitter (dual band variant only)	N-type (f) x 1 (200mW)
3G/12G-SDI bi-directional *(SD/6G-SDI)	HD-BNC (SDI1)
3G-SDI bi-directional *(SD/6G-SDI)	HD-BNC x 2 (SDI2/3)
3G-SDI input *(SD/6G-SDI)	HD-BNC (SDI4 in)
SD/HD/3G-SDI output *(6G-SDI)	HD-BNC (SDI4 out)
*SFP socket	SFP slot (12G-SDI MSA compliant)
*ASI input	HD-BNC
ASI output	HD-BNC
Serial data and power output	4-way circular
Power input	4-way circular
Balanced audio input	5-way circular x 2
Battery pass-through	V-Lock or Anton Bauer plates
Ethernet	RJ45
*USB 2.0 host	USB type-A

Camera Control Option

Camera interface	14-way circular
Tally	5-way circular
RF input	SMA (403-473MHz)

DVB-T Modulation

DVB-T bandwidth	8MHz, 7MHz and 6MHz modes
DVB-T dual pedestal	2x8MHz, 2x7MHz and 2x6MHz modes
DVB-T FEC	1/2, 2/3, 3/4, 5/6, 7/8
DVB-T constellation	QPSK, 16QAM, 64QAM
DVB-T guard interval	1/4, 1/8, 1/16, 1/32
DVB-T bitrates	3.732Mbps to 50Mbps

Input Video Format

*SD input format	SMPTE-259M 720x576i 50Hz 720x480i 59Hz
HD input format	SMPTE-292M/424M 1920x1080i 60/50Hz *59.94Hz 1920x1080p 60/59.94/50/30/29.97/25/ 24/23.97Hz *(1920x1080psf 30/29.97/25/24/23.97Hz) 1280x720p 60/59.94/50/30/29.97/25/2 4/23.97Hz
Ultra HD input format	SMPTE ST-2081/2082 3840x2160p 60/50Hz *(59.94/30/29.94/25/24/23.97Hz)

Encoder/Decoder

HEVC compression	HEVC/H.265/MPEG-H Part 2 *8-bit or 10-bit, *4:2:0 or 4:2:2
*H.264 compression	AVC/H.264/MPEG-4 Part 10

Eclipse

HEVC Outside Broadcast Transmitter

Technical Specification (cont.):

Audio

Analogue audio input	Two balanced analogue stereo pairs from -60dBu to +18dBu
Analogue phantom power	12V/48V
Digital audio input	1.5G/3G/12G-SDI de-embedding *(SD/6G-SDI)
Sample rate	48kHz
Coding modes	Up to eight channels (2-pairs) LPCM 16-bit *(20/24-bit) *AAC MP1 layer 1/2

Other

*RS232 data input	1k2 to 115k2, 7/8 bit, no/odd/even parity
Control panel	Built-in OLED with six buttons

*Encryption

Standard	ABS 32-bit
Licensed	AES 128/256 (subject to export control)

Power

DC input	9.2V to 17.8V reverse polarity protected
Power consumption	Less than 25W typ. @100mW RF power with 4K video

Environment

Temperature range	-10°C to +50°C
Humidity	Less than 85% non-condensing

Physical

Dimensions	L 181mm (165mm excluding connectors) W 110mm D 46mm (without battery plates) or D 85mm (with V-Lock plates) or D 77mm (with Anton Bauer plates)
Dimensions (dual band)	L 193mm (177mm excluding connectors) W 115mm D 46mm (without battery plates) or D 85mm (with V-Lock plates) or D 77mm (with Anton Bauer plates)
Weight	1.4kg (approx.)

Frequency

114150	1.14-1.50GHz
167235	1.67-2.35GHz
198270	1.98-2.70GHz
440500	4.40-5.00GHz
550600	5.50-6.00GHz
198750D	1.98-2.70GHz + **6.40-7.50GHz

** COFDM TX only

Software License Code

SILVER (included)	DVB-T Modulation, Streaming, HD H.265 Encoder
ECLIPSE-GOLD	4K UHD Encoder, *Quad HD Video
*SDRAPP-MESH	SDR Application IP Mesh
*AES128TX	AES 128-Bit Encryption
*AES256TX	AES 256-Bit and 128-Bit Encryption

* Future development

Export of encrypted products is subject to regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Herndon (Headquarters)
2303 Dulles Station Boulevard
Suite 205
Herndon, VA
20171, USA

T: +1 800 665 4648

DTC – Tampa
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 1489 566 750

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #05-06
Singapore
138562

T: +65 6339 0508