

SOL7HDRX

SOLO7 HD Receiver

Overview:

The SOLO7 Diversity Receiver is a compact digital diversity receiver in a durable, compact and lightweight housing, suitable for use in both remote and fixed location applications.

The SOL7HDRX is available with integral band-specific downconverters, or as the SOL7HDRX-015085 which also allows the user to connect external downconverters to the unit.

Control is achieved via the on board Field Controller (FCON) on the front panel, serial RS232 control protocol, USB, or by connecting the unit to an IP network using the Ethernet interface. The product has an easy to use web-based graphical display diagnostic capability to show link quality, enabling users to optimise transmission performance.

An on-board Micro SD card enables local recording of SD Narrowband video possible. Playback and downloading of recorded video is via the Ethernet interface.



Features and Benefits:

Small size: 145 x 95 x 40 mm (excluding cables)

Integral band-specific downconverters

H.264, MPEG-4 ASP and MPEG-2 decoding

Low power

Fully featured 8/7/6/2.5/1.25*/0.625* MHz demodulation

Maximum ratio combining antenna diversity

IP video streaming (RTSP and UDP) *

Internal recording to 32GB SD card (SD Narrowband only)*

Ethernet, Front Panel and USB control

AES128/AES256 decryption (optional)

*Licensable Features

Product Information:

Product Includes

CA0002	12VDC power lead Lemo-wire
CA0023	Standard 12V power block
CA0122	AV cable BNC/phono
CA0063	Control cable
CA2396	BNC to SDI cable

Accessory Options (sold separately)

AP000481	UK mains power lead for CA0023
AP001483	US mains power lead for CA0023
AP004634	EU mains power lead for CA0023
AP007192	AU mains power lead for CA0023
AP007250	Standard USB-A to mini-B cable
AP009137	Tracer 12V 8Ah lithium polymer battery pack
AP009138	Tracer 12V 4Ah lithium polymer battery pack
CA3237	Tracer battery to 4W 0B Lemo cable
Antennas	Various - see Frequency specification
Downconverters	Various - see Frequency specification (015085 only)
CA2544/CA2545/CA2546	SMA-TNC (m-m) LBC195 cable 3m/1m/10m

SOL7HDRX

SOLO7 HD Receiver

Technical Specification:

Inputs

RF input from ANT 1	SMA female 50Ω
RF input from ANT 2	SMA female 50Ω
Power	4-way Lemo

Outputs

S-Video, RS232 data	16-way Hirose
Stereo line level audio & composite video	5-way Lemo
Headphone audio out	3.5mm headphone jack
Serial control	Micro USB
Ethernet	RJ45
HD-SDI/ASI (switchable)	DIN1.0/2.3

Control

Local	RS232/USB Front panel
Remote	Ethernet

Modulation

DVB-T bandwidth	8/7/6MHz
DVB-T guard	1/32, 1/16, 1/8, 1/4
DVB-T FEC	1/2, 2/3, 3/4, 5/6
DVB-T modulation	QPSK, 16QAM, 64QAM
DVB-T sensitivity	-95dBm
Narrowband bandwidth	2.5/1.25*/0.625* MHz
Narrowband guard	1/8, 1/16
Narrowband FEC	1/3, 2/3
Narrowband modulation	QPSK, 16QAM
Narrowband sensitivity	-95 to -104 dBm

Audio

AV	Consumer line level
Headphone	Headphone level

Video

Line standard	PAL/NTSC
Resolution	H.264 SD 704, 528, 480, 352
Resolution (HD)	1280x720p @ 60/59.94/50 1920x1080i @ 60/59.94/50 1920x1080p @ 60/59.94/50/30/29.97/25/24/23.98 1920x1080psF @ 60/59.94/50/30/29.97/25/24/23.98
Coding mode	MPEG2 SD/HD 4:2:2* or 4:2:0 MPEG4 Part 2 ASP (DTC proprietary) H.264 SD/HD 4:2:2* or 4:2:0
Video latency	80ms typically

RF

Tuning step size	250kHz
------------------	--------

Power

DC input	6V to 16V
Power consumption	10W

Decryption

Standard	ABS 32-bit
Licensed	AES 128/256-bit (subject to export control)

Physical

Size	145mm (L) x 95mm (W) x 40mm (D)
Weight	650g
Operating temperature range	-10°C to +45°C

*Licensable features

SOL7HDRX

SOLO7 HD Receiver

Technical Specification (cont.):

Frequency

015085	150-850 MHz
100150	1.00-1.50 GHz
165238	1.65-2.40 GHz
217250	2.17-2.50 GHz
310370	3.10-3.70 GHz
440500	4.40-5.00 GHz
550595	5.50-5.95 GHz

Software License Code

Silver (included)	DVB-T, MPEG2 (inc. HD), H.264 (inc. HD)
Gold	Silver plus Narrowband 2.5MHz & 1.25MHz, MPEG-4, IP Decoding, Recording & Streaming (SD/Narrowband Recording Only), SDI Ancillary Data
Platinum	Gold plus Ultra-Extreme Narrowband 625kHz
AES128RX	AES 128-bit decryption
AES256RX	AES 256-bit and AES 128-bit decryption

Export of encrypted products is subject to regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Herndon (Headquarters)
2303 Dulles Station Boulevard
Suite 205
Herndon, VA
20171, USA

T: +1 800 665 4648

DTC – Tampa
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 1489 566 750

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #05-06
Singapore
138562

T: +65 6339 0508