


# PRORXD-2RU

## Professional Dual Channel Receiver and Decoder

### Overview:

The excellent RF performance is complemented by an extremely flexible decoding platform, with low-delay SD and HD MPEG2 and H.264 decoding ensuring compatibility with all Domo Broadcast and most third party encoders. An optional second decoder can be enabled, allowing two SD or HD signals to be decoded. Multiple output formats are offered with composite and SDI outputs in SD and HD-SDI including embedded audio. ASI transport stream in/out is available and HDMI outputs are provided for use with domestic TVs. A comprehensive graphical on screen display (OSD) is available for monitoring and diagnostics, which can be enabled or disabled separately on the two video outputs.



### Features and Benefits:

Single 8-way or dual 4-way diversity COFDM receiver – maximal ratio combining across all RF inputs for maximum sensitivity and flexibility

Dual SD/HD MPEG-2 and MPEG-4 4:2:2 decoding capability – option to decode two HD signals simultaneously

Composite SD/HD-SDI, HDMI outputs plus ASI in/out

IP streaming out

B&B and tri-level genlock supported

News gathering/SNG vehicles

Events coverage

Video assist

### Product Information:

#### Product Includes

CA0512	External XLR audio cable
CA0649*	External 12V 6.67A 80W desktop PSU

\* Requires AC cable

#### Accessory Options (sold separately)

AP000481	UK power cable for CA0649
AP001483	US power cable for CA0649
AP004634	EU power cable for CA0649
AP007192	AU power cable for CA0649
PRORXDSRFP-2RU	Single rack front panel extender 2RU
PRORXCPLKT-2RU	PRORXD-2RU coupling kit
DCB/DCBGS	Downconverters - various bands available
Antennas	Various frequencies available
CABRF1/3/10	TNC/TNC 50Ω RF cable. 1, 3 or 10m lengths
BNCBNC5/10	BNC/BNC 75Ω ultra flexible cable. 5 or 10m lengths

#### Related Documents

100167	PRORXD Broadcast Receiver User Guide
100224	PRORXD-2U-Quick-Start-Guide

# PRORXD-2RU

## Professional Dual Channel Receiver and Decoder

### Technical Specification

#### Inputs

Power	XLR4 (m)
RF	BNC (50-850MHz) x 8
ASI In	BNC x 2
IFB	XLR3 (f)
Genlock	BNC
RS232 Control	9-way D-type on optional breakout cable

#### Output

2x CBVS/SDI/HD-SDI Video	BNC x 2
HDMI	HDMI type A x 2
ASI Out	BNC
Audio	XLR3 (m), 2 x 5-pin 0B Lemo x 4
RS232 Data	9-way D-type on optional breakout cable x 2

#### Video (dual decoding option)

Resolutions (SD)	PAL/NTSC
Resolutions (HD)	720p50, 720p59, 720p60, 1080i50, 1080i59, 1080i60, 1080p23, 1080p24, 1080p25, 1080p29, 1080p30, 1080p50, 1080p59, 1080p60, 1080psf23, 1080psf24, 1080psf25, 1080psf29, 1080psf30
Decoding mode	H.264 SD/HD 4:2:0/4:2:2 MPEG2 SD/HD 4:2:0/4:2:2 MPEG-4 Part 2 ASP (DTC proprietary)
Delay	From 15ms end-to-end (mode dependent)

#### Audio

Switchable output	Two stereo pairs of balanced analogue audio or two balanced AES/EBU (four channels) per decoder
Analogue output	Stereo pairs +18dBm (on 600 ohm) - two on XLR and two on Lemo
AES/EBU	Two stereo balanced pairs (110 ohm)
Sample rate	48KHz
Format	MPEG audio layer 1 or 2 64kbps to 384kbps

#### Ethernet

Mode	10/100 Ethernet ports x 2
Function	Remote control via web-browser UDP/RTSP streaming over IP

#### ASI

Mode	Byte or burst mode
------	--------------------

#### Data Interfaces

RS232 data output	1K2 to 115K2 baud switchable
Features	GPS data extraction

#### Control

Remote control	Network web browser control interface
Local control	Front panel display with navigation keys
On screen display	Spectrum, RX SNR, RX power

#### Physical

Dimension	220mm (W), 320 mm (D), 88mm (H)
Weight	2.7kg

#### Power

DC input	9V to 26V reverse polarity protected
Power consumption	27-49W (down converter dependent)

#### Environment

Temperature range	-20°C to +60°C
-------------------	----------------

# PRORXD-2RU

## Professional Dual Channel Receiver and Decoder

### Technical Specification (con't):

#### Software License Code

Silver (included)	DVB-T, Video Decoder, SD Only (MPEG-2, H.264-SD), Ultra Mobile Video Link (UMVL)
Gold	Silver plus Narrowband 2.5MHz & 1.25MHz (H.264-HD & MPEG-4 ASP), Second Decoder, IP Streaming, IP Decoding, SDI Ancillary Data
Platinum	Gold plus Narrowband 625kHz, 4:2:2
PRORXD-DEC2	Enable Second HD Decoder
PRORXD-UP	Two-Way Diversity Upgrade
RX-PACDIV-UP	ASI Packet Diversity
AES128PRORX	AES 128-Bit Decryption
AES256PRORX	AES 256-Bit and AES 128-Bit Decryption

Export of encrypted products is subject to United Kingdom regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email [solent.enquiries@domotactical.com](mailto:solent.enquiries@domotactical.com)

**DTC – Herndon (Headquarters)**  
 2303 Dulles Station Boulevard  
 Suite 205  
 Herndon, VA  
 20171, USA

T: +1 800 665 4648

**DTC – Tampa**  
 3845 Gateway Centre Boulevard  
 Suite 360  
 Pinellas Park, FL  
 33782, USA

T: +1 727 471 6900

**DTC – Solent**  
 Fusion 2, 1100 Parkway  
 Solent Business Park  
 Whiteley, Hampshire  
 PO15 7AB, UK

T: +44 1489 566 750

**DTC – Randers**  
 Haraldsvej 64B  
 DK-8960  
 Randers SØ  
 Denmark

T: +45 8791 8100

**DTC – Singapore**  
 21 Media Circle  
 Infinite Studios #05-06  
 Singapore  
 138562

T: +65 6339 0508