

NETNode2x2W-5PT-175500T

NETNode IP Mesh Radio Phase 5 (Plain Tri-Band)

Overview:

Phase 5 is the latest generation of DTC's NETNode IP Mesh Radio family, offering built-in dual HD video encoders and MIMO capability, providing our highest ever data capacities and maximum frequency flexibility. The latest tri-band product offers increased frequency agility with support for high L-band, S-band and C-band, provided by one physical unit. NETNode IP Mesh Radios can be combined in a fluid self-forming, self-healing mesh network containing up to 80 nodes. The tri-band radios exchange bidirectional IP data in a single RF channel, or can utilise different frequency channels for the uplink and downlink traffic, thereby, simplifying frequency management in a complex network. The entire mesh can operate in a bandwidth from 1.25MHz to 20MHz, employing DTC's unique COFDM modulation scheme. Multiple Input Multiple Output (MIMO) technology transmits two signals in the same channel, almost doubling the available data capacity, can also be configured in standard Mesh.



Features and Benefits:

- Self-forming, self-healing mesh architecture
- Ideal for use for wide area coverage & multi-hop, mobile applications such as robotics and city wide infrastructure
- Tri-band capability offered in L-band (1.70-1.85GHz), S-band (2.2-2.5GHz) and C-band (4.4-4.9GHz)
- 4G IP connectivity for additional backhaul offering beyond mesh
- Low latency IP communication
- Fan cooled with three 25mm fans
- Inbuilt Field Controller interface
- Configurable RF bandwidth from 1.25MHz to 20MHz
- Data capacity up to 90Mbps in 20MHz channel bandwidth
- Interlink mode for enhanced capability and large scale systems
- 64Gb of on-board storage with store & forward functionality
- Built in encryption (DES as standard, AES128/256 subject to export control)
- Mission Commander compatibility

Product Information:

Product Includes

CA0002	12VDC power lead Lemo 3m
CA0023	12V power block, requires IEC cable

Accessory Options (sold separately)

AP000481	UK IEC power supply cable
AP001483	US IEC power supply cable
AP004634	EU IEC power supply cable
AP007192	AU IEC power supply cable
AP009131	USB GPS receiver, GlobalSat BU-353-S4
CA3303	Mesh 26-way control cable 1m
CA3304	Mesh 26-way talkback audio cable 1m
CA3305	Mesh 26-way second Ethernet cable 150mm
*MISCDRTAC	Mission Commander Tactical application for desktop or tablet
*MCS	Mission Commander Strategic advanced client/server application
SOL8SDI	HDMI or composite video to SDI converter

* Refer to separate datasheet

Related Documents

Resource ID 100232	NETNode Phase 5 Hardware Guide
High Bandwidth Mesh – P5	Phase 4 and 5 Mesh Comparison

NETNode2x2W-5PT-175500T

NETNode IP Mesh Radio Phase 5 (Plain Tri-Band)

Technical Specification:

Interfaces

COFDM RF interfaces	SMA x 4 (2 x TX/RX, 2 x RX)
USB type-A	USB type A
Power	4-way Lemo 0B
Ethernet	RJ45 and on 26-way D-type
Config & data	26-way high density D-type
LED	Bi-colour
Control interface	Internal FCON based controller
HD-SDI video	DIN 1.0/2.3 x 2

Typical Range

NLOS light urban	800-1400m typical
LOS (e.g. ground to air)	50km+

RF Interfaces

Antenna A	Channel 1 receive only
Antenna B	Channel 1 switched transmit/receive
Antenna C	Channel 2 receive only
Antenna D	Channel 2 switched transmit/receive

RF and Modulation

Tuning step size	125kHz step
Output power	+33dBm per channel in 0.25dB step (4W total)
Bandwidth	1.25, 1.5, 1.75, 2.5, 3.0, 3.5, 5.0, 6.0, 7.0, 8.0, 10.0MHz (video and IP Mesh) 12.0, 14.0, 16.0, 20.0MHz (IP Mesh only)
Mesh capacity	Up to 87Mbps MIMO, 17Mbps standard Mesh
Modulation	COFDM 360 carrier modulation
Carrier modulation	BPSK/QPSK/16QAM/64QAM (adaptive)
FEC rate	FEC 1/2, FEC 2/3 (adaptive)
Receive diversity	Maximum ratio combining
Receive sensitivity	-98dBm (BW 2.5MHz/QPSK 1/2)

IP Interface

Primary Ethernet	1Gbit/s Ethernet
Secondary Ethernet	10/100 Ethernet
IP address allocation	DHCP dynamic IP addressing/static IP

Streaming

Format	UDP multicast/unicast RTSP/RTP/UDP multicast/unicast ONVIF Profile S
MJPEG	TCP/HTTP

Video

Video input	Video streams via IP camera and HD-SDI inputs
-------------	---

Store and Forward Options

Storage format	SD card interface (Secure Digital card) - not user accessible
Record options	Continuous or triggered (Milestone)
Files download	From web browser interface/RTSP
Video and audio clip size	30 seconds

Encryption

Standard	DES
Licensed	AES128/AES256 (subject to export control)

Data Interface

RS232/RS485 bi-directional data (shared with user camera control)	1K2 to 115K2 baud switchable with UDP and TCP routing protocol
---	--

NETNode2x2W-5PT-175500T

NETNode IP Mesh Radio Phase 5 (Plain Tri-Band)

Technical Specification (con't):

PTZ Camera Interface

User camera type	IP camera
User camera control	Mission Commander PC application using VISCA, PELCOD or PELCOP

Control

Local control	LEDs power and Mesh status FCON front panel
Remote control	Web browser GUI Mission Commander - control of all parameters in a map based application

Power

DC input (12V)	8-18V
Power consumed (non-MIMO)	12W approx.
Power consumed (MIMO)	25W (40W pk) approx.

Physical

Size	135mm x 89mm x 35mm (421cu cm, 25.7 cu inch)
Weight	550g

Environment

Temperature range	-20°C to +50°C
-------------------	----------------

Frequency

175500	L-band (1.70-1.85GHz), S-band (2.20-2.50GHz), C-band (4.40-4.90GHz)
--------	---

Software License Code

Silver (included)	Standard Mesh, MIMO Mesh, DES encryption, recording and streaming
Gold	Silver plus SD H.264 encoder
Platinum	Gold plus HD H.264 encoder
IAS-NETNode2x2W-5PT	Interference Avoidance Scheme
AES128NN	AES 128-Bit Encryption
AES256NN	AES 256-Bit and 128-Bit Encryption

Export of encrypted products is subject to United Kingdom regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Herndon (Headquarters)
2303 Dulles Station Boulevard
Suite 205
Herndon, VA
20171, USA

T: +1 800 665 4648

DTC – Tampa
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 1489 566 750

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #05-06
Singapore
138562

T: +65 6339 0508